



AGRI 30 AVR

PORTABLE POWER
Power take off Range AGRI

PRODUCT ADVANTAGES

- Reinforced chassis
- AVR: Automatic Voltage Regulation
- Inclusive differential protection
- Made in France

AGRI GEN The main advantages of this control system are as follows:• Large backlit screen for optimum reading in all conditions. Screen protected by a plastic visor. Easy to use with two navigation buttons.• Electrical measurement test (voltage, frequency, kW, kVA).• Statistics stored in the memory (max. Voltage, max. frequency, etc.).• Events list memory (low frequency, etc.).• Alarm for min. and max. voltage, min. and max. frequency, overload, short-circuit, etc.• Remote control available via the application. AVR By regulating the voltage electronically by $\pm 2\%$, depending on the model, the AVR eliminates all risk of damage to boilers or certain kinds of electronic equipment.

Range AGRI

The solution to energy production via a tractor power take-off



POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Inlet Temperature, of a barometric pressure of 100 kPA (100 m A.S.L.), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.

AGRI 30 AVR

GENERAL SPECIFICATIONS

Range	AGRI
Frequency (Hz)	50 Hz
Continuous Nominal Rating 40°C (kVA)	30
Standby Rating 27°C (kVA)	32.50
Voltage (V)	400/230
Number of Phase	Three phase

ALTERNATOR SPECIFICATIONS

Number of pole	4
Number of wires	12
AVR Regulation	Yes
Indication of protection	IP 23
Insulation class	H

PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 230V 16A socket - circuit breaker + 1 400V 63A socket - circuit breaker + Residual Current Device + AGRI GEN

TRACTOR SPECIFICATIONS

Input speed	430
Engine power kW	31
Engine power HP	41

DIMENSIONS AND WEIGHT

Length (cm)	117.80
Width (cm)	94.60
Height (cm)	103
Dry Weight (kg)	235

PACKAGING

Packaging type	
Length (cm)	120
Width (cm)	94.60
Height (cm)	116
Weight (kg)	245

KOHLER®

SDMO®

AGRI 30 AVR

ACCESSORIES SUPPLIED



User and maintenance manual



Two connecting pins

OPTIONS



VERSO10T63

The three-phase 63 A manual changeover switch enables an alternator mounted on the power take-off to be connected to a building and control the source of current in the event of insufficient power or mains supply return.



RPM

Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V



RPQ1

For earthing your generator set. Galvanised 1 m long spike, supplied with 10 m of 25 mm² cable.



FM63A

Male plugs 63A - 400V



CARDAN33

Final drive shaft Power take-off shaft with free-wheel

KOHLER®

SDMO®

7/22/2019

AGRI 30 AVR - PORTABLE POWER - Power take off AGRI

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 - France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com