



TRASH 3

PORTABLE POWER

Water Pumps Range AQUALINE SPECIALIST

PRODUCT ADVANTAGES

- KOHLER air-cooled industrial engine
- Resistant pump-barrel
- Automatic priming
- Easy access to the turbine
- Offers accessories

Range AQUALINE SPECIALIST

High performance under extreme conditions.



TRASH 3

WATER PUMP SPECIFICATIONS

| | |
|--|---|
| Range | AQUALINE SPECIALIST |
| Type liquid | Extremely heavily sedimented water pump |
| Suction diameter [mm] | 76 |
| Backflow diameter (mm) | 76 |
| Outflow maximum (L/min) | 1083.33 |
| Outflow maximum (m3/h) | 65 |
| Lifting height (m) | 25 |
| Suction height (m) | 8 |
| Granulometry (mm) | 20 |
| Automatic priming | Yes |
| Fuel | Diesel Fuel |
| Tank (L) | 4.30 |
| 75% cons. (l/h) * | 1.40 |
| 75% Autonomy (h) * | 3.10 |
| Sound power level guaranteed LwA dB(A) | 110 |
| Acoustic pressure level @1m in dB(A) | 95 |
| Acoustic pressure level @7m in dB(A) | 81 |

ENGINE SPECIFICATIONS

| | |
|---|---------------|
| Engine brand | KOHLER DIESEL |
| Engine ref. | KD350 |
| Distribution | Diesel O.H.V. |
| Start | Starter |
| Oil shutdown | Non |
| Displacement (cm3) | 349 |
| Oil system capacity including filters (L) | 1.20 |

DIMENSIONS AND WEIGHT

| | |
|-----------------|-------|
| Length (cm) | 71.50 |
| Width (cm) | 57 |
| Height (cm) | 59 |
| Dry Weight (kg) | 67 |

PACKAGING

| | |
|------------------------------------|--------|
| Packaging type | Box |
| Length (cm) | 73 |
| Width (cm) | 58 |
| Height (cm) | 59.50 |
| Weight (kg) | 79 |
| Pallet type | 120/80 |
| Number of box by pallet | 4 |
| Pallet height (cm) | 132 |
| weight of the packaged Pallet (kg) | 326 |

ACCESSORIES SUPPLIED



Inlet filter

Fast connections



Circlips

User and maintenance manual



OPTIONS



RKB2 Trolley kit for the generating sets superior to 6kW



RH1 Cover for SDMO 's generating sets, welding sets and water pumps