



TRASH 4

PORTABLE POWER

Water Pumps Range AQUALINE SPECIALIST

PRODUCT ADVANTAGES

- KOHLER air-cooled industrial engine
- Resistant pump-barrel
- Automatic priming
- Easy access to the turbine
- Offers accessories

Range AQUALINE SPECIALIST

High performance under extreme conditions.



TRASH 4

WATER PUMP SPECIFICATIONS

Range	AQUALINE SPECIALIST
Type liquid	Extremely heavily sedimented water pump
Suction diameter [mm]	100
Backflow diameter (mm)	100
Outflow maximum (L/min)	1600
Outflow maximum (m ³ /h)	96
Lifting height (m)	17
Suction height (m)	8
Granulometry (mm)	20
Automatic priming	Yes
Fuel	Diesel Fuel
Tank (L)	4.30
75% cons. (l/h) *	1.40
75% Autonomy (h) *	3.10
Sound power level guaranteed LwA dB(A)	110
Acoustic pressure level @1m in dB(A)	95
Acoustic pressure level @7m in dB(A)	81

ENGINE SPECIFICATIONS

Engine brand	KOHLER DIESEL
Engine ref.	KD350
Distribution	Diesel O.H.V.
Start	Starter
Oil shutdown	Non
Displacement (cm ³)	349
Oil system capacity including filters (L)	1.20

DIMENSIONS AND WEIGHT

Length (cm)	71.50
Width (cm)	57
Height (cm)	59
Dry Weight (kg)	90

PACKAGING

Packaging type	Box
Length (cm)	73
Width (cm)	58
Height (cm)	59.50
Weight (kg)	102
Pallet type	120/80
Number of box by pallet	4
Pallet height (cm)	132
weight of the packaged Pallet (kg)	418



3/25/2019

TRASH 4 - PORTABLE POWER - Water Pumps AQUALINE SPECIALIST

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 - France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com

ACCESSORIES SUPPLIED



Inlet filter

Fast connections



Circlips

User and maintenance manual



OPTIONS



RKB2 Trolley kit for the generating sets superior to 6kW



RH1 Cover for SDMO 's generating sets, welding sets and water pumps