

ST 2.36 C5

PORTABLE POWER

Water Pumps Range AQUALINE INTENS

PRODUCT ADVANTAGES

- HONDA Professional Engine
- Automatic priming
- Offeres accessories

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range AQUALINE INTENS

Designed for water with low solid content.



ST 2.36 C5

WATER PUMP SPECIFICATIONS

Range	AQUALINE INTENS
Type liquid	Clear water with little sediment pump
Suction diameter [mm]	50
Backflow diameter (mm)	50
Outflow maximum (L/min)	600
Outflow maximum (m3/h)	36
Lifting height (m)	29
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Yes
Fuel	Petrol
Tank (L)	2
75% cons. (l/h) *	1
75% Autonomy (h) *	2
Sound power level guaranteed LwA dB(A)	103
Acoustic pressure level @1m in dB(A)	87
Acoustic pressure level @7m in dB(A)	72

ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX120_C5
Distribution	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	118
Oil system capacity including filters (l)	0.60

DIMENSIONS AND WEIGHT

Length (cm)	46.80
Width (cm)	36.20
Height (cm)	38
Dry Weight (kg)	23

PACKAGING

Packaging type	Box
Length (cm)	48.50
Width (cm)	38.50
Height (cm)	40
Weight (kg)	24.50
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	133
weight of the packaged Pallet (kg)	304

ACCESSORIES SUPPLIED



Inlet filter



Screw-on connectors



Circlips



User and maintenance manual

OPTIONS



RBH1

Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)



RBH0-5

Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).



RHO

Cover for SDMO 's generating sets, welding sets and water pumps



R11

Piping kit for 2 water pumps made up of 5m suction + 25m lift.