

## ST 3.60 C5

PORTABLE POWER

Water Pumps Range AQUALINE INTENS

### PRODUCT ADVANTAGES

- HONDA Professional Engine
- Automatic priming
- Offeres accessories

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

### Range AQUALINE INTENS

Designed for water with low solid content.



## ST 3.60 C5

### WATER PUMP SPECIFICATIONS

Range	AQUALINE INTENS
Type liquid	Clear water with little sediment pump
Suction diameter [mm]	76
Backflow diameter (mm)	76
Outflow maximum (L/min)	900
Outflow maximum (m3/h)	54
Lifting height (m)	26
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Yes
Fuel	Petrol
Tank (L)	3.10
75% cons. (l/h) *	0.90
75% Autonomy (h) *	3.40
Sound power level guaranteed LwA dB(A)	105
Acoustic pressure level @1m in dB(A)	90
Acoustic pressure level @7m in dB(A)	75

### ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX160_C5
Distribution	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	163
Oil system capacity including filters (l)	0.60

### DIMENSIONS AND WEIGHT

Length (cm)	50.50
Width (cm)	41.40
Height (cm)	44.80
Dry Weight (kg)	29

### PACKAGING

Packaging type	Box
Length (cm)	52
Width (cm)	42.50
Height (cm)	46.50
Weight (kg)	32
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	153
weight of the packaged Pallet (kg)	394

### ACCESSORIES SUPPLIED



Inlet filter



Screw-on connectors



Circlips



User and maintenance manual

### OPTIONS



**RBH1**

Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)



**RBH0-5**

Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).



**RHO**

Cover for SDMO 's generating sets, welding sets and water pumps



**R12**

Piping kit for 3 water pumps made up of 5 m suction + 25 m lift.