



XT 3.78 C5

PORTABLE POWER

Water Pumps Range AQUALINE SPECIALIST

PRODUCT ADVANTAGES

- HONDA Professional Engine
- Easy acces to the turbine (without tools)
- Automatic priming
- Resistant pump-barrel
- Offeres accessories

Range AQUALINE SPECIALIST

High performance under extreme conditions.



XT 3.78 C5

WATER PUMP SPECIFICATIONS

Range	AQUALINE SPECIALIST
Type liquid	Extremely heavily sedimented water pump
Suction diameter [mm]	76
Backflow diameter (mm)	76
Outflow maximum (L/min)	1340
Outflow maximum (m3/h)	80.40
Lifting height (m)	27
Suction height (m)	8
Granulometry (mm)	27
Automatic priming	Yes
Fuel	Petrol
Tank (L)	5.30
75% cons. (l/h) *	2
75% Autonomy (h) *	2.70
Sound power level guaranteed LwA dB(A)	110
Acoustic pressure level @1m in dB(A)	94
Acoustic pressure level @7m in dB(A)	80

ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX240_C5
Distribution	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	242
Oil system capacity including filters (l)	1.10

DIMENSIONS AND WEIGHT

Length (cm)	69
Width (cm)	48.50
Height (cm)	53.20
Dry Weight (kg)	58

PACKAGING

Packaging type	Box
Length (cm)	72
Width (cm)	52
Height (cm)	58
Weight (kg)	68.50
Pallet type	120/80
Number of box by pallet	4
Pallet height (cm)	129
weight of the packaged Pallet (kg)	284



7/2/2020

XT 3.78 C5 - PORTABLE POWER - Water Pumps AQUALINE SPECIALIST

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 - France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com

ACCESSORIES SUPPLIED



Inlet filter



Screw-on connectors



Circlips



User and maintenance manual

OPTIONS



RHO

Cover for SDMO 's generating sets, welding sets and water pumps



R12

Piping kit for 3 water pumps made up of 5 m suction + 25 m lift.