



## TR 2.36 H

PORTABLE POWER

Water Pumps Range AQUALINE INTENS

### PRODUCT ADVANTAGES

- HONDA Professional Engine
- Resistant pump-barrel
- Automatic priming
- Easy access to the turbine
- Offers accessories

The AQUALINETM INTENS TR 2.36 H and TR 3.60 H models have a very high quality pump body and are designed for treating dirty water intensively and reliably. The front cover can be removed for quick cleaning, which is a considerable help for professionals.

### Range AQUALINE INTENS

Designed for water with low solid content.



## TR 2.36 H

### WATER PUMP SPECIFICATIONS

Range	AQUALINE INTENS
Type liquid	Heavily sedimented water pump
Suction diameter [mm]	50
Backflow diameter (mm)	50
Outflow maximum (L/min)	600
Outflow maximum (m3/h)	36
Lifting height (m)	29
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Yes
Fuel	Petrol
Tank (L)	2
75% cons. (l/h) *	1
75% Autonomy (h) *	2
Sound power level guaranteed LwA dB(A)	103
Acoustic pressure level @1m in dB(A)	87
Acoustic pressure level @7m in dB(A)	72

### ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX120
Distribution	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	118
Oil system capacity including filters (L)	0.60

### DIMENSIONS AND WEIGHT

Length (cm)	46.80
Width (cm)	36.20
Height (cm)	39.80
Dry Weight (kg)	23

### PACKAGING

Packaging type	Box
Length (cm)	48
Width (cm)	38
Height (cm)	41.50
Weight (kg)	26.50
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	138
weight of the packaged Pallet (kg)	328

# KOHLER®

# SDMO®

## TR 2.36 H

### ACCESSORIES SUPPLIED



Inlet filter



Screw-on connectors



Circlips



User and maintenance manual

### OPTIONS



**RBH1** Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)



**RBH0-5** Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).



**RHO** Cover for SDMO 's generating sets, welding sets and water pumps



**R11** Piping kit for 2 water pumps made up of 5m suction + 25m lift.