

POWER PRODUCTS-50 HZ

OCEANIC

Type	kVA		Engine	Open version		Enclosure	Enclosed version		
	PRP (1)	ESP (2)		Dimensions Lxwxh (m)	Weight (kg) (3)		Dimensions Lxwxh (m)	Sound level dB(A)7m	Weight (kg) (3)
D275	250	275	P126TI	2.90x1.30x1.67	2340	M227	4.00x1.38x2.15	73	3190
D300	273	300	P126TI	2.90x1.30x1.67	2410	M227	4.00x1.38x2.15	73	3260
D330	300	330	P126TI-II	3.16x1.34x1.59	2570	M228	4.48x1.41x2.43	71	3670
D440	400	440	P158LE	3.47x1.50x1.83	2910	M229	5.03x1.56x2.44	75	4090
D550	500	550	DP158LD	3.47x1.50x1.82	3220	M229	5.03x1.56x2.44	74	4262
D630	573	630	DP180LA	3.47x1.63x1.97	3700	M230	5.03x1.69x2.66	78	5381
D700	631	694	DP180LB	3.47x1.63x2.16	3700	M230	5.03x1.69x2.66	78	5381
D830	750	825	DP222LC	3.47x1.63x2.18	4080	M230	5.03x1.69x2.66	78	5670

NEVADA

GZ50	-	50	GMC850	2.20x1.04x1.17	786	SSE25-60	2.59x1.08x1.51	62	1100
GZ60	-	59	GMC857	2.20x1.04x1.17	786	SSE25-60	2.59x1.08x1.51	62	1100
GZ80	-	87	GMC857T	2.80x1.12x1.38	1271	SSE80-150	3.53x1.15x1.72	64	1518
GZ100	-	92	GMC857T-IC	2.80x1.12x1.38	1271	SSE80-150	3.53x1.15x1.72	65	1539
GZ125	-	127	PSI88T	2.80x1.12x1.54	1293	SSE80-150	3.53x1.15x1.72	70	1732
GZ150	-	146	PSI88T-IC	2.80x1.12x1.54	1554	SSE80-150	3.53x1.15x1.72	70	1863
GZ180	160	176	D111TIC-176	3.58x1.35x1.85	2238	SSE180-200	4.35x1.39x2.10	68	3064
GZ200	196	216	D111TIC-195	3.58x1.35x1.85	2238	SSE180-200	4.35x1.39x2.10	68	3213
GZ250	250	275	D146T-IC	3.50x1.75x2.00	2942	SSE250	4.53x1.79x2.46	64	3711
GZ300	300	330	D183TIC-273	3.47x1.68x2.38	3623	SSE300-350	6.31x2.23x2.86	64	5926
GZ350	318	350	D183TIC-319	3.47x1.68x2.38	3623	SSE300-350	6.31x2.23x2.86	64	5926
GZ400	345	380	D219TIC	3.90x1.98x2.38	3888	SSE400	7.23x2.49x2.86	65	6429

PACIFIC

T1250	1136	1250	S12R-PTA	4.33x2.00x2.37	9736	ISO20SI*	6.06x2.44x2.90	80	14220
T1400	1275	1403	S12R-PTA	4.33x2.00x2.37	10076	ISO20SI*	6.06x2.44x2.90	80	14932
T1540	1400	1540	S12R-PTA2	4.42x2.00x2.37	10296	ISO20SI*	6.06x2.44x2.90	80	15307
T1650	1500	1600	S12R-PTAA2	4.98x2.25x2.46	10870	-	-	-	-
T1650C	1500	1650	S12R-F1PTAW2	5.09x2.20x2.39	12043	ISO20SI*	6.06x2.44x2.90	89	17307
T1900	1727	1900	S16R-PTA	5.52x2.29x2.48	12979	ISO40*	12.19x2.44x2.90	83	22760
T2100	1909	2100	S16R-PTA2	5.60x2.29x2.48	12979	ISO40*	12.19x2.44x2.90	84	19660
T2200	2050	2255	S16R-PTAA2	5.60x2.29x2.56	14215	ISO40*	12.19x2.44x2.90	85	23090
T2200C	2000	2200	S16R-F1PTAW2	4.58x1.90x2.39**	12160	ISO40*	12.19x2.44x2.90	85	22700
T2500	2273	2500	S16R2-PTAW	6.09x2.36x2.40	15500	CPU40SI*	12.19x2.44x2.90	82	TBC
T2500C	2273	2500	S16R2-F1PTAW	6.09x2.36x2.40	15500	CPU40SI*	12.19x2.44x2.90	82	TBC
T2650	2413	2650	S16R2-PTAW-E	6.09x2.36x2.40	16000	-	-	-	-

KD SERIES

KD800 ⁽⁴⁾	727	800	KD27V12	4.19x1.75x2.28	5470	M427SI*	6.41x2.16x2.75	77	8300
KD900 ⁽⁴⁾	818	900	KD27V12	4.19x1.75x2.28	5910	M427SI*	6.41x2.16x2.75	77	8400
KD1000 ⁽⁴⁾	909	1000	KD27V12	4.19x1.75x2.28	6040	M427SI*	6.41x2.16x2.75	77	8800
KD1100 ⁽⁴⁾	1000	1100	KD27V12	4.19x1.75x2.28	6270	M427SI*	6.41x2.16x2.75	78	9000
KD1250 ⁽⁴⁾	1136	1250	KD36V16	4.67x1.90x2.38	8300	M428SI*	6.80x2.16x2.75	79	11600
KD1400 ⁽⁴⁾	1291	1420	KD36V16	4.67x1.90x2.38	8600	M428SI*	6.80x2.16x2.75	79	10800
KD1500 ⁽⁴⁾	1364	1500	KD36V16	4.67x1.90x2.38	8900	M428SI*	6.80x2.16x2.75	79	11100
KD1650 ⁽⁴⁾	1500	1650	KD45V20	5.09x2.12x2.48	10100	ISO20SI*	6.06x2.44x2.90	88	15900
KD1800 ⁽⁴⁾	1636	1800	KD45V20	5.09x2.12x2.48	10800	ISO20SI*	6.06x2.44x2.90	88	16500
KD2000 ⁽⁴⁾	1818	2000	KD62V12	4.74x2.10x2.56**	14938	CPU40SI*	12.19x2.44x2.90	78	29020
KD2250 ⁽⁴⁾	2045	2250	KD62V12	4.74x2.10x2.56**	15186	CPU40SI*	12.19x2.44x2.90	78	29270
KD2500 ⁽⁴⁾	2273	2500	KD62V12	4.74x2.10x2.56**	15637	CPU40SI*	12.19x2.44x2.90	78	29730
KD2800 ⁽⁴⁾	2545	2800	KD62V12	4.74x2.10x2.56**	17045	CPU40SI*	12.19x2.44x2.90	78	30100
KD3100 ⁽⁴⁾	2818	3100	KD83V16	5.32x2.36x2.48**	19750	-	-	-	-
KD3300 ⁽⁴⁾	3000	3300	KD83V16	5.32x2.36x2.48**	20300	-	-	-	-
KD3500 ⁽⁴⁾	3182	3500	KD83V16	5.32x2.36x2.48**	20300	-	-	-	-

SALES OFFICES FRANCE

WEST
SDMO BREST
+33 (0)2 98 41 13 48

CENTRAL WEST
SDMO CHOLET
+33 (0)2 41 75 96 70

PARIS/NORTH & NORMANDY
SDMO ARRAS
+33 (0)3 21 73 38 26

SDMO GENNEVILLIERS
+33 (0)1 41 88 38 00

EAST
SDMO METZ
+33 (0)3 87 37 88 50

SOUTH EAST
SDMO AIX-EN-PROVENCE
+33 (0)4 42 52 51 60

SDMO VALENCE
+33 (0)4 75 81 31 00

SOUTH WEST
SDMO TOULOUSE
+33 (0)5 61 24 75 75

SUBSIDIARIES

GERMANY
SDMO GMBH
+49 (0)63 32 97 15 - 0

LATIN AMERICA & CARIBBEAN
SDMO GENERATING SETS
+1 305 863 0012

BELGIUM
SDMO NV/SA
+32 36 46 04 15

SPAIN
SDMO INDUSTRIES IBERICA
+34 (9) 35 86 34 00

UK
SDMO ENERGY LTD
+44 (0)12 56 38 68 38

RUSSIA
SDMO MOSCOW
+7 495 665 16 98

OFFICES

SOUTH AFRICA
SDMO SOUTH AFRICA
+27 (0) 8 32 33 55 61

ALGERIA
SDMO ALGIERS
+213 (0) 23 47 05 19

DUBAI
SDMO MIDDLE EAST
+971 4 458 70 20

EGYPT
SDMO CAIRO
+ 20 2 22 67 12 78

TOGO
SDMO WEST AFRICA
+ 228 22 22 63 65

TURKEY
SDMO ISTANBUL
+ 90 53 07 35 09 10

KOHLER-SDMO is a registered trademark of SDMO Industries. Non-contractual document - In accordance with our policy, we may modify, without prior notice, any specifications published in this catalogue. Photo credit: SDMO - Guillaume Bann - 7305



INDUSTRIAL RANGE POCKET GUIDE

50HZ 60HZ
6kVA - 3500kVA / 5kW - 3250kW

THE ENERGY SOLUTION FOR YOUR INDUSTRIAL APPLICATIONS



Tous les produits SDMO sont certifiés par un laboratoire accrédité ISO 17025

KOHLER
IN POWER. SINCE 1920.



INDUSTRIAL RANGEDATA APP.
Windows Phone | Android | iOS

KOHLER
SDMO

SDMO Industries - 270 rue de Kerervern
CS40047 - 29801 Brest cedex 9 - France
Tél. +33 (0)2 98 41 41 41
www.kohler-sdmo.com

KOHLER
SDMO

PP-IN-PG-ML-181

(1) PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1.
(2) ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.
(3) Dry weight : without fuel & without cooling liquid
(4) exist in Fuel Optimized and Emission Optimized
* exists in other enclosure/container with lower sound level
** Dimensions & weight without cooling system (separate aero cooler)
L-R : Long Running / C3 : stage IIIA equivalent (Clean Power Range) / U : 60 hz / M : Monophase / H : High speed (3000 RPM) / C (Clean): Exhaust Emission Optimized
TBC : To Be Confirmed

POWER PRODUCTS-50 HZ

Type	kVA		Engine	Open version		Enclosure	Enclosed version		
	PRP (1)	ESP (2)		Dimensions Lxwxh (m)	Weight (kg) (3)		Dimensions Lxwxh (m)	Sound level dB(A)7m	Weight (kg) (3)
K9	8,1	9	KDW1003	1.22x0.70x0.92	290	M125	1.48x0.76x1.03	54	390
K12	10,9	12	KDW1404	1.41x0.72x1.02	340	M126	1.75x0.78x1.23	54	510
K16	15	16,5	KDW1603	1.41x0.72x1.02	410	M126	1.75x0.78x1.23	61	580
K16H	-	16	KDW1003-H	1.41x0.72x1.02	310	M126	1.75x0.78x1.23	66	480
K21H	-	21	KDW1404-H	1.41x0.72x1.02	350	M126	1.75x0.78x1.23	67	520
K22	19,5	21,5	KDI1903M	1.41x0.72x1.08	490	M126	1.75x0.78x1.23	58	660
K22C3	19,5	21,5	KDI1903M	1.41x0.72x1.08	490	M126	1.75x0.78x1.23	58	660
K27	24,1	26,5	KDI2504M	1.41x0.72x1.08	540	M126	1.75x0.78x1.23	64	710
K33	30	33	KDI2504TM-30	1.70x0.90x1.20	585	M137	2.10x0.94x1.28	63	773
K33C3	30	33	KDI2504TM-30-EU	1.70x0.90x1.20	585	M137	2.10x0.94x1.28	63	773
K44	40	44	KDI2504TM-40	1.70x0.90x1.20	618	M137	2.10x0.94x1.28	64	806
K44C3	40	40	KDI2504TM-40-EU	1.70x0.90x1.20	618	M137	2.10x0.94x1.28	64	806
K66	60	66	KDI3404TM	1.70x0.90x1.17	781	M137	2.10x0.94x1.28	66	978
K6M	5,7	6,4	KDW1003	1.22x0.70x0.92	290	M125	1.48x0.76x1.03	54	390
K10M	8,2	9	KDW1404	1.41x0.72x1.02	350	M126	1.75x0.78x1.23	54	520
K12M	10,7	11,8	KDW1603	1.41x0.72x1.02	440	M126	1.75x0.78x1.23	61	610
K17M	14,1	15,5	KDI1903M	1.41x0.72x1.08	530	M126	1.75x0.78x1.23	58	700
K26M	23,6	26	KDI2504TM-30	1.70x0.90x1.20	690	M137	2.10x0.94x1.28	64	944

T9HK	-	9	L2E-SDH	1.22x0.70x0.92	240	M125	1.48x0.76x1.03	54	360
T12K	10,5	11,5	S3L2-SD	1.41x0.72x1.05	387	M126	1.75x0.78x1.23	58	530
T12HK	-	12	L3E-SDH	1.22x0.70x0.92	260	M125	1.48x0.76x1.03	54	380
T16K	14,5	16	S4L2-SD	1.41x0.72x1.05	406	M126	1.75x0.78x1.23	59	554
T8HKM	-	7,5	L2E-SDH	1.22x0.70x0.92	220	M125	1.48x0.76x1.03	54	340
T9KM	7,8	8,6	S3L2-SD	1.41x0.72x1.05	396	M126	1.75x0.78x1.23	58	544
T11HKM	-	10,5	L3E-SDH	1.22x0.70x0.92	280	M125	1.48x0.76x1.03	54	400
T12KM	10,9	12	S4L2-SD	1.41x0.72x1.05	406	M126	1.75x0.78x1.23	59	630

J22	20	22	3029DFS29	1.70x0.90x1.18	649	M137	2.10x0.94x1.28	62	837
J22LR	20	22	3029DFS29-LR	1.70x0.90x1.18	649	M137	2.10x0.94x1.28	62	837
J33	30	33	3029DFS29	1.70x0.90x1.18	654	M137	2.10x0.94x1.28	62	842
J44K	40	44	3029TFS29	1.70x0.90x1.24	705	M137	2.10x0.94x1.28	62	893
J66K	60	66	4045TF120	1.87x0.99x1.36	995	M128	2.30x1.06x1.68	61	1405
J66C3	60	66	4045HFS85-IND	1.87x0.99x1.36	995	M128	2.30x1.06x1.68	61	1405
J77K	70	77	4045TF120	1.87x0.99x1.36	1038	M128	2.30x1.06x1.68	64	1448
J88K	80	88	4045TF220	1.87x0.99x1.36	1038	M128	2.30x1.06x1.68	66	1448
J110K	100	110	4045HF120	1.95x1.08x1.33	1097	M129	2.55x1.15x1.68	64	1597
J110C3	100	110	4045HFS87-IND	1.95x1.08x1.46	1187	M129	2.55x1.15x1.68	66	1587
J130K	120	132	6068TF220	2.37x1.11x1.48	1498	M226	3.51x1.20x1.83	64	2088
J165K	150	165	6068HF120-153	2.37x1.11x1.48	1578	M226	3.51x1.20x1.83	64	2198
J165C3	150	165	6068HFS85-IND	2.37x2.11x1.48	1578	M226	3.51x1.20x1.83	64	2168
J200K	182	200	6068HF120-183	2.37x1.11x1.48	1726	M226	3.51x1.20x1.83	65	2336
J220K	200	220	6068HSG22	2.37x1.11x1.54	1715	M226	3.51x1.20x1.83	67	2346
J220C3	200	220	6068HFS86-IND	2.40x1.11x1.48	1811	M226	3.51x1.20x1.83	66	2471
J250K	227	250	6068HFS55-228	2.40x1.11x1.54	1800	M226	3.51x1.20x1.83	71	2400

V275C2	250	275	TAD734GE	2.90x1.30x1.59	2200	M227	4.00x1.38x2.15	67	3130
V350C2	318	350	TAD1341GE	3.16x1.34x1.76	3110	M228	4.48x1.41x2.43	71	4042
V350C3	318	350	TAD1351GE	3.16x1.34x1.80	3103	M228	4.48x1.41x2.43	66	4035
V400C2	352	387	TAD1342GE	3.16x1.34x1.80	3060	M228	4.48x1.41x2.43	71	4170
V440C2	400	440	TAD1344GE	3.16x1.34x1.80	3110	M228	4.48x1.41x2.43	71	4080
V440C3	400	440	TAD1355GE	3.16x1.34x1.80	3110	M228	4.48x1.41x2.43	68	4080
V500C2	455	500	TAD1345GE	3.16x1.34x1.80	3250	M228	4.48x1.41x2.43	71	4360
V550C2	500	550	TAD1641GE	3.47x1.50x2.05	3620	M229	5.03x1.56x2.44	66	4870
V550C3	500	550	TAD1651GE	3.47x1.63x2.10	3620	M228	4.48x1.41x2.43	70	4870
V650C2	591	650	TAD1642GE	3.47x1.63x2.09	3780	M230	5.03x1.69x2.66	70	5300
V700C2	650	700	TWD1643GE	3.47x1.63x2.05	3890	M230	5.03x1.69x2.66	75	5550

POWER PRODUCTS-60 HZ

Type	kW		Engine	Open version		Enclosure	Canopied version		
	PRP (1)	ESP (2)		Dimensions Lxwxh (m)	Weight (kg) (3)		Dimensions Lxwxh (m)	Sound level dB(A)7m	Weight (kg) (3)
K9U	7,6	8,4	KDW1003	1.22x0.70x0.92	290	M125	1.48x0.76x1.03	64	390
K12U	10,6	11,6	KDW1404	1.41x0.72x1.02	340	M126	1.75x0.78x1.23	64	510
K16U	14,1	15,5	KDW1603	1.41x0.72x1.02	410	M126	1.75x0.78x1.23	69	580
K20U	17,3	19	KDI1903M	1.41x0.72x1.08	490	M126	1.75x0.78x1.23	67	660
K25U	22,6	24,8	KDI2504M	1.41x0.72x1.08	540	M126	1.75x0.78x1.23	68	710
K30U	28	30,7	KDI2504TM-30	1.70x0.90x1.20	585	M137	2.10x0.94x1.28	63	773
K40U	36	40	KDI2504TM-40	1.70x0.90x1.20	500	M137	2.10x0.94x1.28	68	806
K60U	54	60	KDI3404TM	1.70x0.90x1.17	781	M137	2.10x0.94x1.28	66	978
K9UM	7,3	8	KDW1003	1.41x0.72x1.02	330	M126	1.75x0.78x1.23	64	500
K12UM	10	11	KDW1404	1.41x0.72x1.02	350	M126	1.75x0.78x1.23	64	520
K16UM	12,2	14,5	KDW1603	1.41x0.72x1.02	440	M126	1.75x0.78x1.23	69	610
K20UM	16,4	18	KDI1903M	1.41x0.72x1.08	530	M126	1.75x0.78x1.23	67	700
K30UM	27,3	30	KDI2504TM-30	1.70x0.90x1.20	621	M137	2.10x0.94x1.28	69	830
K40UM	36	40	KDI2504TM-40	1.70x0.90x1.07	636	M137	2.10x0.94x1.28	69	824

T11U	10	11	S3L2-SD	1.41x0.72x1.05	387	M126	1.75x0.78x1.23	65	530
T16U	14	16	S4L2-SD	1.41x0.72x1.05	406	M126	1.75x0.78x1.23	65	554
T11UM	9	10	S3L2-SD	1.41x0.72x1.05	396	M126	1.75x0.78x1.23	63	544
T16UM	14	15	S4L2-SD	1.41x0.72x1.05	406	M126	1.75x0.78x1.23	65	630

J20U	18,2	20	3029DFS29	1.70x0.90x1.18	649	M137	2.10x0.94x1.28	68	837
J30U	27,2	30	3029DFS29	1.70x0.90x1.18	654	M137	2.10x0.94x1.28	68	842
J40U	36	40	3029TFS29	1.70x0.90x1.24	705	M137	2.10x0.94x1.28	66	1040
J60U	54	60	4045TF120	1.87x0.99x1.36	995	M128	2.30x1.06x1.68	67	1405
J70U	64	70	4045TF120	1.87x0.99x1.36	1038	M128	2.30x1.06x1.68	67	1548
J80U	73	80	4045TF220	1.87x0.99x1.36	1038	M128	2.30x1.06x1.68	73	1508
J100U	91	100	4045HF120	1.95x1.08x1.33	1097	M129	2.55x1.15x1.68	70	1587
J120U	106	117	6068TF220	2.37x1.11x1.48	1498	M226	3.51x1.20x1.83	69	2088
J150U	137	150	6068HF120-153	2.37x1.11x1.48	1578	M226	3.51x1.20x1.83	69	2168
J175U	159	175	6068HF120-183	2.37x1.11x1.48	1726	M226	3.51x1.20x1.83	69	2320
J200U	182	200	6068HF475	2.40x1.11x1.48	1766	M226	3.51x1.20x1.83	70	2390
J20UM	18,2	20	3029DFS29	1.70x0.90x1.18	688	M137	2.10x0.94x1.28	68	876
J30UM	25,5	28	3029DFS29	1.70x0.90x1.18	723	M137	2.10x0.94x1.28	68	911
J40UM	36	40	3029TFS29	1.70x0.90x1.24	719	M137	2.10x0.94x1.28	67	907
J60UM	55	60	4045TF120	1.95x1.08x1.33	1097	M129	2.55x1.15x1.68	67	1497

V250U	227	250	TAD734GE	2.90x1.30x1.59	2260	M227	4.00x1.38x2.15	74	3190
V300U	273	300	TAD1341GE	3.16x1.34x1.76	3110	M228	4.48x1.41x2.43	76	4042
V350U	319	350	TAD1342GE	3.16x1.34x1.80	3060	M228	4.48x1.41x2.43	76	4170
V400U	364	400	TAD1344GE	3.16x1.50x1.80	3110	M228	4.48x1.41x2.43	76	4360
V500UC2	455	500	TAD1641GE	3.47x1.50x2.05	3620	M229	5.03x1.56x2.44	75	4870
V550UC2	500	550	TAD1642GE	3.47x1.63x2.09	3650	M230	5.03x1.69x2.66	75	5170
V600UC2	546	600	TWD1643GE	3.47x1.63x2.05	4020	M230	5.03x1.69x2.66	79	5550

- (1) PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1.
 (2) ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.
 (3) Dry weight : without fuel & without cooling liquid
 (4) exist in Fuel Optimized and Emission Optimized
 * exists in other enclosure/container with lower sound level
 ** Dimensions & weight without cooling system (separate aero cooler)
 L-R : Long Running / C3 : stage IIIA equivalent (Clean Power Range) / U : 60 hz / M : Monophase / H : High speed (3000 RPM) / C (Clean): Exhaust Emission Optimized
 TBC : To Be Confirmed

POWER PRODUCTS-60 HZ

Type	kW		Engine	Open version		Enclosure	Enclosed version		
	PRP (1)	ESP (2)		Dimensions Lxwxh (m)	Weight (kg) (3)		Dimensions Lxwxh (m)	Sound level dB(A)7m	Weight (kg) (3)
D250U	227	250	P126TI	2.90x1.30x1.67	2410	M227	4.00x1.38x2.15	78	3260
D300U	273	300	P126TI-II	3.16x1.34x1.59	2570	M228	4.48x1.41x2.43	75	3670
D400U	364	400	P158LE	3.47x1.50x1.83	2910	M229	5.03x1.56x2.44	79	4090
D500U	449	494	DP158LD	3.47x1.50x1.82	3220	M229	5.03x1.56x2.44	80	4262
D550U	500	550	DP180LA	3.47x1.63x1.97	3465	M230	5.03x1.69x2.66	82	5146
D600U	545	600	DP180LB	3.47x1.63x2.16	3700				